

Lessons Learned from 12 Years of Laboratory Conversions to VAV and Control Retrofits



GWELIN PALIAGA, TAYLOR ENGINEERING GPALIAGA@TAYLOR-ENGINEERING.COM

Learning Objectives

- Plan renovation projects where energy conservation pays for improved ventilation and safety
- Plan renovation projects that add today's BAS technology to existing mechanical equipment, enhancing access to information needed to manage safety, energy use and mechanical maintenance.
- Extend the capacity of existing primary systems by upgrading constant volume labs to VAV.
- Reduce the potential for chemical exposure in labs by bringing today's aerodynamic design


ASHRAE is a registered Provider with The American Institute of Architects Continuing Education Systems. Credit earned on completion of this program will be reported to ASHRAE Records for AIA members. Certificates of Completion for non-AIA members are available on request.

This program is registered with the AIA/ASHRAE for continuing professional education. As such, it does not include content that may be deemed or construed to be an approval or endorsement by the AIA of any material of construction or any method or manner of handling, using, distributing, or dealing in any material or product. Questions related to specific materials, methods, and services will be addressed at the conclusion of this presentation.

ATLANTA 2015 – SEMINAR 11

SLIDE 2

Why focus on labs?




ATLANTA 2015 – SEMINAR 11

SLIDE 3

Lab Retrofit process: Three Phases


Initial Assessment

- Benchmarking
 - High level audit
- Not all high users are good candidates*
12 buildings use 33% electricity




Detailed Study

- Targeted TAB
- As-builts
- Calibrated simulation
- Cost estimate



Implementation

- Construction
- Commissioning
- M&V, Rebates




ATLANTA 2015 – SEMINAR 11

SLIDE 4

Laboratory Retrofit Opportunities: High Cost

- Medium to High Capital Cost Measures
 - DDC to the Zone
 - Convert systems to VAV (supply, exhaust, hoods)
 - Add heat recovery (often difficult in retrofit)
 - Stack airflow reduction based on wind tunnel analysis
 - Bring non-lab zones up to current energy code standards



ATLANTA 2015 – SEMINAR 11

SLIDE 5

Laboratory Retrofit Opportunities: Lower Cost

- Low Capital Cost (RCx Opportunities)
 - Fix economizers
 - Fix AHU controls
 - Fix leaking valves/dampers
 - Rebalance airflows
 - Convert constant flow HW and CHW to variable flow
 - Recalibrate or replace critical control sensors (a.k.a. money sensors)
 - Update sequences if DDC
 - Fault detection & alarming

ATLANTA 2015 – SEMINAR 11

SLIDE 6

Completed Projects

- Start with constant volume labs
 - VAV to the zone
 - Demand based resets: temperature, pressure
 - VAV hoods where it makes sense
 - Fume stack dispersion study and reduced flow
 - VAV fume stack flow where possible
 - RCx and smaller energy measures easily piggyback on a large retrofit project
- Then convert pneumatic VAV labs to DDC
 - DDC control retrofit
 - Demand based resets
 - Fume stack dispersion and reduced flow
 - Re-commissioning

ATLANTA 2015 – SEMINAR 11

SLIDE 7

Representative results of CAV to VAV conversion Gilbert Hall

Energy Cost Savings

Pre-retrofit utility cost	\$1,750,000
2012-2013 utility cost	\$804,000
Utility Cost Savings	54%

First Costs & Payback


First Costs	\$3,300,000
Utility rebate	\$710,000
Net cost	\$2,590,000
Simple Payback	2.7 years



ATLANTA 2015 – SEMINAR 11

SLIDE 8

Measured Energy Savings



Non-Energy Benefits


- Fume dispersion study identifies issues, particularly with small stacks
- Less noise
- Higher comfort
- Fume hood safety improvements
- Better control of room pressurization
- Feedback and alarming for better management

ATLANTA 2015 – SEMINAR 11

SLIDE 10

What is next?

Lab of the future




ATLANTA 2015 – SEMINAR 11

SLIDE 11

Lab Of the Future Measures

- hood**
 - Face Velocity Setback
 - Face Velocity Limit
 - Hood Minimum Reduction
 - Auto Sash Closers
- room**
 - Air Change Setback
 - Central Demand Controlled Ventilation



ATLANTA 2015 – SEMINAR 11

SLIDE 12

Measure: Face Velocity Setback

- Reduce velocity from 100 to 60 fpm when no users detected
- ASHRAE 110 testing
- Benefits
 - Energy
 - Usage data
 - Safety
- Barriers: None




ATLANTA 2015 – SEMINAR 11

SLIDE 13

Measure: Face Velocity Limit

- Limit average face velocity to 120 fpm
- Safety:
 - Turbulence & reduced containment at higher speed
 - Impact on room pressure
- Minimize unnecessary energy use
- Barriers: None

"Higher face velocities do not result in greater protection as might be supposed." -- ACGIH



● ANSI/ASHRAE Z9.5 & NFPA: 80 – 120 fpm ● ACGIH & NRC: 80 – 100 fpm ● UC Guide: 125 fpm max

ATLANTA 2015 – SEMINAR 11

SLIDE 14

Measure: Hood Minimum Reduction

- Reduce flow when sash closed
- ANSI Z9.5-2012 LEL/LFL limits
 - Up to 50% reduction over NFPA-45 2004
- LEL/LFF Calculation per hood
- Barriers: None




ATLANTA 2015 – SEMINAR 11

SLIDE 15

Measure: Auto Sash Closers

- Automatically close sash when not in use
- Benefits
 - Safety
 - Energy
 - Sound
 - Simplifies fire life safety design
- Barriers: user acceptance, cost




ATLANTA 2015 – SEMINAR 11

SLIDE 16

Measure: Auto Sash Closers

- Sash management:



ATLANTA 2015 – SEMINAR 11

SLIDE 17


Auto Sash Closers: Life Safety benefit

- Can program sashes to automatically close on a signal from the fire panel
- This reduces the DP across the doors
- It also eliminates (or greatly reduces) the need for MAU
- Better containment of fumes if there is a spill during unoccupied hours (e.g. earthquake)

ATLANTA 2015 – SEMINAR 11

SLIDE 18


Typical Lab Design



ATLANTA 2015 – SEMINAR 11

SLIDE 19


Typical Lab Design – Fire Mode



ATLANTA 2015 – SEMINAR 11

SLIDE 20

Typical Lab Design – Fire Mode



ATLANTA 2015 – SEMINAR 11

SLIDE 21

Measure: Air Change Setback

OCCUPIED

Why 6 or higher ACH?

- 6 ACH is common EH&S guideline
- Driven by chemical inventory & spill analysis



UNOCCUPIED

Why 4 ACH?


- Minimum per ANSI Z9.5 2012, OSHA 1990, ASHRAE, NFPA-45 2004
- Numerous precedents



ATLANTA 2015 – SEMINAR 11

SLIDE 22


Measure: Air Change Setback



ATLANTA 2015 – SEMINAR 11

SLIDE 23


Lab of the Future Study Buildings



ATLANTA 2015 – SEMINAR 11

SLIDE 24

Interactive Effects



ATLANTA 2015 – SEMINAR 11

SLIDE 25

Energy Cost Savings

Measure	Energy Cost Savings (\$/yr)		
	Gilbert	Lokey	Moore
Air Change Setback	\$14,000	\$10,000	\$12,000
Auto Sash Closers	\$17,000	\$263,000	\$77,000
Face Velocity Setback	\$14,000	\$216,000	\$64,000
Hood Minimum Reduction	\$0	\$20,000	\$2,000
Face Velocity Limit	\$5,000	\$22,000	\$18,000
All but Face Velocity Setback	\$38,000	\$301,000	\$95,000

Package with largest savings potential

ATLANTA 2015 – SEMINAR 11

SLIDE 26

Simple Payback

Measure	Simple Payback (yr)		
	Gilbert	Lokey	Moore
Air Change Setback	3	4	1
Auto Sash Closers	9	3	3
Face Velocity Setback	2	1	1
Hood Minimum Reduction	-	0	1
Face Velocity Limit	1	1	0
All but Face Velocity Setback	5	3	3

ATLANTA 2015 – SEMINAR 11

SLIDE 27

Economic Results

Measure	Energy Cost Savings (\$/yr)			First Cost (\$)		
	Gilbert	Lokey	Moore	Gilbert	Lokey	Moore
Air Change Setback	\$14,000	\$10,000	\$12,000	\$43,000	\$40,000	\$18,000
Auto Sash Closers	\$17,000	\$263,000	\$77,000	\$149,000	\$869,000	\$253,000
Face Velocity Setback	\$14,000	\$216,000	\$64,000	\$26,000	\$150,000	\$44,000
Hood Minimum Reduction	\$0	\$20,000	\$2,000	\$1,000	\$8,000	\$2,000
Face Velocity Limit	\$5,000	\$22,000	\$18,000	\$6,000	\$19,000	\$7,000
All but Face Velocity Setback	\$38,000	\$301,000	\$95,000	\$199,000	\$935,000	\$280,000

Measure	Simple Payback (yr)			Net Present Value (\$)			Internal Rate of Return (%)		
	Gilbert	Lokey	Moore	Gilbert	Lokey	Moore	Gilbert	Lokey	Moore
Air Change Setback	3	4	1	\$87,000	\$51,000	\$89,000	32%	23%	67%
Auto Sash Closers	9	3	3	\$8,000	\$1,527,000	\$447,000	4%	29%	29%
Face Velocity Setback	2	1	1	\$102,000	\$1,818,000	\$538,000	55%	145%	147%
Hood Minimum Reduction	-	0	1	-\$1,000	\$170,000	\$17,000	-	249%	92%
Face Velocity Limit	1	1	0	\$41,000	\$180,000	\$160,000	85%	118%	272%
All but Face Velocity Setback	5	3	3	\$149,000	\$1,807,000	\$581,000	15%	91%	33%

ATLANTA 2015 – SEMINAR 11

SLIDE 28

What if we remove Air Change Setback?

Measure	Energy Cost Savings (\$/yr)		
	Gilbert	Lokey	Moore
Air Change Setback	\$14,000	\$10,000	\$12,000
Auto Sash Closers	\$17,000	\$263,000	\$77,000
Face Velocity Setback	\$14,000	\$216,000	\$64,000
Hood Minimum Reduction	\$0	\$20,000	\$2,000
Face Velocity Limit	\$5,000	\$22,000	\$18,000
All but Face Velocity Setback	\$38,000	\$301,000	\$95,000
	\$19,000	\$0	\$82,000


Gilbert: 50% reduction in potential savings

ATLANTA 2015 – SEMINAR 11

SLIDE 29

Conclusions & Summary

- CV to VAV Conversions
 - 30-55% energy savings
 - Improved: Safety, comfort, acoustics
- Advanced Airflow controls
 - \$0.40-\$3.00/ft² savings above VAV lab (5-36%)
 - 3-5 year payback
 - Improved safety



ATLANTA 2015 – SEMINAR 11

SLIDE 30

Questions

Gwelen Paliaga
gpaliaga@taylor-engineering.com



ATLANTA 2015 – SEMINAR 11

SLIDE 31